



## COLOUR-ENHANCER SEALER, WET EFFECT

Solvent-based enhancing and stain protection treatment. It does not create a film and does not give the surface a polished appearance. Approved for food contact.



SOLVENT BASE



ENHANCER



APPROVED FOR  
FOOD CONTACT

### TECHNICAL CHARACTERISTICS

Penetrating product, strong revitalising properties, low-emission odourless solvent base. Penetrates the material micro-pores, creating a barrier against dirt and stains. The product fulfils EC Regulation CE 10/2011 for food contact (Report no. 3882).

### HOW TO APPLY IT

#### Tools



Paintbrush, spraying, cloth or sponge, airless spray pump, single-brush machine.

#### Mode

The product must be applied on a perfectly clean and dry surface using a brush, a cloth or a sponge, or an airless sprayer. For large surfaces the use of a single-brush machine with adequate disc is recommended to simplify the application of the product and the removal of excess product residues. Apply the product evenly. After 10 minutes rework any unabsorbed product on the surface. Remove any excess using paper or a clean cloth. For best results, repeat the treatment after about 15 minutes from the first application. In case of floors, wait at least 24 hours before walking on them.

**IMPORTANT:** the product must be applied at an ambient temperature between 10 and 30 °C, away from direct sunlight. Before treating the whole surface, test the product on a hidden corner.

### WHERE TO APPLY IT

- GRANITE**
- MARBLE**
- STONE**
- QUARTZ AGGLOMERATE**
- CEMENT AGGLOMERATE**



### PLUS/ADVANTAGES

- LOW VOC EMISSIONS**
- ODOURLESS**
- GREAT ENHANCING PROPERTIES AND STAIN PROTECTION**
- HIGH LONG-LASTING RESISTANCE**
- FACILITATES CLEANING AND MAINTENANCE**
- NO YELLOWING**

### TECHNICAL DATA

Density at 25°C gr/ml	1,005
Appearance	opalescent liquid
Standard colour	colourless

### COVERAGE

**The consumption depends greatly on the porosity of the material**

SMOOTH OR BRUSHED SURFACES	20-30 m²/lt
POLISHED SURFACES	40 m²/lt

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



[Click or scan  
for more info](#)

**MADE in ITALY**

AT YOUR DISPOSAL  
**TENAX.IT**

### PACKAGING

0,25-l litre.

### HOW TO STORE IT

Under normal conditions of use and work, the product stored properly away from heat, moisture and direct sunlight is guaranteed 24 months. Carefully seal the packaging after use.

### WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. If the surface is treated for the first time, we recommend that you assess the effect and the adherence of the material on a sample or hidden corner.

### LEGISLATION

Before use, please read the instructions on the safety data sheet and the notes found on the container.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.