



## DARKENING TREATMENT FOR BLACK GRANITE

It is applied to even and enhance the colour and improve the surface of black granite.



SOLVENT BASE



ENHANCER

### TECHNICAL CHARACTERISTICS

For professional use only. Usually applied on slabs, it corrects the defects of white flakes, oil stains and excessively grey background colour of black granites.

### HOW TO APPLY IT

#### Tools

Roller

#### Mode

Smooth the material to grain 800 and dry in the oven or in the open air for one or two days. BLACK67 should be applied by roller leaving a slight excess (50g/m<sup>2</sup>). Allow the product to dry for at least 48-72 hours (shorter time if with an oven or in particularly hot climates). Carry out the final polishing using silicone carbide brushes, then proceed with Gr1200 and LUX with polishing heads. Before proceeding, test the product on a sample, or an out of sight corner. Shake well before use.

### WHERE TO APPLY IT

**BLACK GRANITE**


### PLUS/ADVANTAGES

- ⊕ EVENS AND INCREASES THE COLOUR OF THE MATERIAL
- ⊕ COVERS THE TYPICAL DEFECTS OF BLACK GRANITES
- ⊕ FOR PROFESSIONAL USE ONLY

### TECHNICAL DATA

Density at 25°C gr/ml 0.96

Appearance liquid

Standard colour black

### COVERAGE

**1L of product** 20 m<sup>2</sup>  
215 sq.ft.

BEFORE

AFTER

### PACKAGING

1-5 litres.

### HOW TO STORE IT

Under normal use and work conditions, when stored far from heat sources, humidity and direct sunlight, the product is guaranteed for 24 months. Accurately close the pack after use.

### WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. If the surface is treated for the first time, we recommend that you assess the effect and the adherence of the material on a sample or hidden corner.

### LEGISLATION

Before use, please read the instructions on the safety data sheet and the notes found on the container.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



Scans to  
access  
multimedia  
contributions